



## PRODUCT DESCRIPTION

The ALPHA LED STRIP LIGHT is mainly for commercial use and is the ideal replacement for uorescent T8 and T5HO fixtures. The strip light can be used in warehouses, offices, garages, retail shops, and other commercial applications.

Our ALPHA LED STRIP LIGHT are backed with our industry-leading 100,000-hour rated lamp life and 5 to 10 year warranty. Contact us for pricing or more information.

## PRODUCT SPECIFICATION

### FEATURES

- End-to-end mounting and wiring
- Seamless surface mounting application
- Linkable to 8FT strip xture
- Diused lighting distribution
- Minimize labor and recycling costs
- Espen dimmable driver
- Acrylic drop lens that delivers low glare
- 80% more energy saving compared to traditional lamps
- Simple and secure installation
- Housing: Aluminum/PC
- Limited Warranty: 5 YRS, 10YR Optional

### TECHNICAL DATA

1. CCT: 4000K-5000K
2. Color Rendering Index (CRI): >80
3. Operation Temperature: -20°C to 50°C
4. Eciency: 130LPW
5. Universal voltage: 120V-277V applications
6. Input Frequency: 50/60Hz
7. High power factor: .90
8. Rated Life: 100,000 hrs
9. LED: SMT 2835 chips

## PRODUCT SPECIFICATION

Product No.	Wattage (W)	Input Voltage	Color Temp (K)	Rated Lumens	Rated Efficacy	CRI	Beam Angle	Rated Life (Hours)	Operating Temp. (°F)	Power Factor
<b>4FT ALPHA LED STRIP LIGHT</b>										
AL-STP4-24W	24	120V -277V, 50/60 Hz	3500K/ 4000K/5000K	3120	>130	>80	120°	100,000	-20°C to 50°C	>.90
AL-STP4-36W	36	120V -277V, 50/60 Hz	3500K/ 4000K/5000K	4630	>130	>80	120°	100,000	-20°C to 50°C	>.90
AL-STP4-40W	40	120V -277V, 50/60 Hz	3500K/ 4000K/5000K	5200	>130	>80	120°	100,000	-20°C to 50°C	>.90
AL-STP4-42W	42	120V -277V, 50/60 Hz	3500K/ 4000K/5000K	5460	>130	>80	120°	100,000	-20°C to 50°C	>.90
AL-STP4-48W	48	120V -277V, 50/60 Hz	3500K/ 4000K/5000K	6240	>130	>80	120°	100,000	-20°C to 50°C	>.90
AL-STP4-56W	56	120V -277V, 50/60 Hz	3500K/ 4000K/5000K	7280	>130	>80	120°	100,000	-20°C to 50°C	>.90
AL-STP4-68W	68	120V -277V, 50/60 Hz	3500K/ 4000K/5000K	8840	>130	>80	120°	100,000	-20°C to 50°C	>.90
<b>8FT ALPHA LED STRIP LIGHT</b>										
AL-STP8-60W	60	120V -277V, 50/60 Hz	3500K/4000K/ 5000K	7800	>130	>80	120°	100,000	-20°C to 50°C	>.90
AL-STP8-68W	68	120V -277V, 50/60 Hz	3500K/4000K/ 5000K	8840	>130	>80	120°	100,000	-20°C to 50°C	>.90


## PHYSICAL DATA

Product No.	Material Usage	Certification	Packing/carton	LxWxD inch
AL-STP4-24W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	6	48"x3.35"x3.56"
AL-STP4-36W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	6	48"x3.35"x3.56"
AL-STP4-40W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	6	48"x3.35"x3.56"
AL-STP4-42W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	6	95.9"x3.35"x3.56"
AL-STP4-48W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	6	95.9"x3.35"x3.56"
AL-STP4-56W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	6	95.9"x3.35"x3.56"
AL-STP4-68W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	6	95.9"x3.35"x3.56"
AL-STP8-60W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	2	95.9"x3.35"x3.56"
AL-STP8-68W	RoHS Compliant; no mercury	DLC V4.2, UL, cUL and Lighting Facts	2	95.9"x3.35"x3.56"

### DIMENSIONS



### MOUNTING OPTIONS



- A - Keyhole Slots for Surface Mounting
- B - Wiring Knockouts
- C - T-Bar Clip Mounting Hole
- D - V-Hook Openings for Chain Mounting

### DIMMING CONNECTION

